

Transport Incubator-TINC15

Product Model : **TINC15**



Category: Baby Care Equipment, Medical Equipment, Transport Incubator,

Specification :

- **Control Panel:** The controller features a display that is easy to read at any angle during transport. Display for air and skin temperature help you maintain, control and provide essential information about the infant's thermal support. Microprocessor controlled system with air and skin modes of operation. Display both temperatures i. e. Air/Skin temp along with Set temp. Soft touch operation with digital display and extensive alarms.
- **Alarms**
 - Skin temp low / high • Probe failure • Low battery • Power failure • System Failure • Timer

In case of high temperature i.e. above 38°C, heater automatically cuts off thus ensuring baby's safety. Can be used on manual mode as well.
- **Collapsible Stainless Steel Stand:** With 2/4 no. gas springs for ambulance and in hospital transport purposes. Gas spring system allow the stand to collapse when the lever is pulled and trolley is pressed from both the sides.
- **Performance characteristics**

Temperature set range	: 32.0°C - 39.0°C
Temp variability	: 1.0°C
Temp uniformity	: 1.0°C
Air filter	: removes airborne particles & dust
- **Easy Access:** Quick and easy access through the side access door and front port holes. The side

door folds down and the mattress retracts out from the hood to access for emergency procedures. The door and tubing ports offer ventilator tubing support. Infant restraint strap attached to the baby bed.

- **Power Source:** Transport incubator operates on AC or DC power using AC when available or switching to its internal battery when necessary
Battery : The batteries used in the system are 12 volt 18ah. Sealed maintenance free VRLA batteries.
Charge Time : 8-10 hrs. per battery from full discharge.
Hood options : Standard single wall / double wall hood (on demand).
Chassis Body : Plastic (fibre) to shock proof the system
- **Standard Features**
 - Single wall Hood • Skin temperature probe / Air temp. Probe • 2 access doors • 1 baby belt • Collapsible trolley
- **Optional**
 - Examination lamp • 2 disposable infant restraint straps • 1 iris port • 6 tubing ports • Accessory shelf
 - Suction, Oxygen cylinder, pressure regulatory assembly, Flow Meter, Remote Controlled movement of the Trolley.
- **Control Displays**
 - Battery condition status : single led indication of low battery condition on the side panel
 - Power mode : illuminates AC, DC or external DC
 - Air/Baby temp °C : displays incubator air temp / baby temperature
- **Dimensions in inches (Approx.)**
 - Height without hood : 39"
 - In collapsible stand mode : 29"
 - height with hood : 49"
 - Width : 23"
 - Length : 53"
 - Baby bed : 20x11"
 - Weight : 75kg
 - Backup : 60-90mins
 - Size of Castors : 5" PU

Sealed maintenance free battery : VRLA Batteries Charge time : 10hrs.(Approx.)

Legacy of Excellence in Health Care...



Corp Office: 712, 7th Floor Ocus Quantum Sector 51 Gurugram 122003 (Hr.) India
Reg Office: UG9, 1st Floor Ocus Quantum Sector 51 Gurugram 122003 (Hr.) India



info@gwsmed.com, gwssurgicals@gmail.com



+91-124-4915548



www.gwsmed.com